# HP LaserJet M1319 Multifunction Printer series



Get outstanding value with HP's lowest-priced MFP that combines efficient copy, scan, and fax capabilities with high-quality laser printing. Compact, easy to use and packed with innovative features to enhance performance.



HP LaserJet M1319f
Multifunction Printer

**An excellent choice for micro- and small-business customers who are looking to print, copy, scan and fax with one affordable device. Ideal for customers who want a full-featured, high-quality fax machine and printer.**

**Get great value and ease of use with HP's lowest-priced MFP with faxing capability.**
Make your budget go further with this MFP's low purchase price. Print, copy, scan and fax: save money with just one device. Simplify multitasking with this easy-to-use MFP which features an intuitive two-line control panel. Enjoy consistent print quality with All-in-one Original HP print cartridges which are clean and easy to install and remove. Save space: this compact MFP is easy to place and use where you need it. Get peace of mind with HP's proven LaserJet quality and reliability.

**Get more done with performance that boosts your productivity.**
No-wait Instant-on Technology delivers a first printed page out as fast as 8.5 seconds from idle mode. Instant-on Copy with LED-based technology delivers your first copy in seconds too. Copy effortlessly with a 30-sheet automatic document feeder and enjoy the flexibility of a 10-sheet priority slot for alternative media and envelopes. Protect your MFP from theft with a Kensington lock that is easily connected to the device. Handle complex jobs with a powerful 240 MHz processor.

**Experience increased functionality with this MFP's integrated design and innovative features.**
Use your MFP as a phone with the integrated handset. Fast advanced 33.6 kbps faxing includes FaxTel feature and 500-page fax storage capacity. Private receive fax allows you to store faxes securely on the device until you want to print them. Quickly dial your most used numbers with fax speed dial. Reduce paper waste and time handling unwanted faxes with junk fax blocker, available for customers with caller ID service. Automatic copy collation saves you the effort of sorting documents manually.

# Technical specifications

| | | |
|---|---|---|
| **Print technology** | Monochrome Laser | |
| **Print speed** | A4 black: Up to 18 ppm. First page out black: < 8.5 sec (from ready mode). Exact speed varies depending on the system configuration, software program and document complexity | |
| **Processor** | 240 MHz. Tensilica® | |
| **Memory** | 32 MB. Not expandable | |
| **Print** | Quality | REt, HP FastRes 1200 |
| | Resolution | A4 black: Up to 1200 x 1200 dpi |
| | Printer languages | Host based |
| | Economical printing | Economode (saves toner), N-up printing (saves paper) |
| | Typefaces/fonts | None (Host-based) |
| | Duty cycle (monthly, A4) | Up to 8000 pages |
| | Print margins (mm) | Top: 4 mm. Left: 4 mm. Right: 4 mm. Bottom: 4 mm |
| **Fax** | Modem speed | 3 sec per page |
| | Telecom compliance | Telecom: TBR-21: 1998; EG 201 121: 1998, FCC Part 68, Industry Canada CS03, NOM-151-SCTI-1999 (Mexico), PTC-200 (New Zealand), AS/ACIF S002: 2001 (Australia), IDA PSTN1 (Singapore), TPS002-01 (Malaysia), IG 0005-11 (Taiwan), HKTA 2011 (Hong Kong SAR), YD514, YD/T589, YD703, GB3382 (China) |
| | Fax memory | Up to 500 |
| | Fax resolution | Standard: 203 x 98 dpi. Fine: 203 x 196 dpi. Superfine: 300 x 300 dpi (no halftone) |
| | Quick dialing | Up to 120. 10 one-touch front panel keys |
| **Scan** | Type | Sheetfed LED Scanner. Colour scanning: Yes. File Formats: JPEG, TIFF, BMP, GIF, PDF, PNG |
| | Scan resolution | Optical: Up to 600 dpi. Enhanced: Up to 19200 dpi |
| | Bit depth | 24-bit |
| | Grey scale levels | 256 |
| | Twain version | TWAIN compatible Version 1.9 |
| | Scannable area | Maximum media size: 21.6 x 38.1 cm |
| | Margins for scanned items | Left: 4 mm. Top: 4 mm. Right: 4 mm. Bottom: 4 mm |
| | Scanner smart software features | Colour scan up to 600 dpi optical, 19200 dpi interpolated. TWAIN/WIA scan drivers with image editing. CIS, 600 dpi, 24-bit colour, Sheet-feed ADF only (30-sheets) |
| **Copy** | Copy speed | Black: Up to 18 cpm (ADF copy speed is up to 14 cpm) |
| | Copy resolution | Up to 600 x 600 dpi |
| | Multiple copies | Up to 99 |
| | Reduce/enlarge | 25 to 400% |

| **Media handling** | **Input:** | **Capacity** | **Weight** | **Size** |
|---|---|---|---|---|
| | Tray 1 | sheets: 250, envelopes: 10, transparencies: 10 | 60 to 163 g/m² | A4, A5, B5, C5, C6, DL, 16K, 76 x 127 to 216 x 356 mm |
| | ADF | sheets: 30 | 48 to 105 g/m² | Minimum: 148 x 105 mm (A6), Maximum: 215.9 x 355.6 mm (legal) |
| | **Output:** | Sheets: Up to 100. Envelopes: Up to 10. Transparencies: Up to 10 | | |
| | **Duplex printing:** | Manual (driver support provided) | | |

*hp* ®

# Technical specifications

| | |
|---|---|
| **Media types** | Paper (plain, preprinted, prepunched, bond, colour, glossy, letterhead, light, heavy, recycled, rough), envelopes, vellum, transparencies, labels, cardstock |
| **Interface and connectivity** | Hi-Speed USB (compatible with USB 2.0 specifications) |
| **Memory card compatibility** | None |
| **Operating systems compatibility** | Microsoft® Windows® 2000, XP Home, Server 2003; Windows Vista® Ready; Mac OS X v10.3, v10.4 or higher; Linux. Latest drivers available from http://www.hp.com |
| **Minimum system requirements** | Microsoft® Windows® 2000, Server 2003: any Pentium® II processor or higher, 64 MB RAM, 250 MB hard disk space, SVGA 800 x 600 with 16-bit colour display, Internet Explorer 5.5 or higher (full install), CD-ROM drive, USB port (print driver, scan driver only); Microsoft® Windows® XP-32 Home, XP-32 Professional: any Pentium® II processor (Pentium® III or higher recommended), 128 MB RAM, 250 MB hard disk space, SVGA 800 x 600 with 16-bit colour display, Internet Explorer 5.5 or higher (full install), CD-ROM drive, USB port; Microsoft® Windows® XP-x64: any Pentium® II processor (Pentium® III or higher recommended), 128 MB RAM, 250 MB hard disk space, SVGA 800 x 600 with 16-bit colour display, Internet Explorer 5.5 or higher (full install), CD-ROM drive, USB port; Windows Vista®-32 Home, -32 Professional: 1 GHz processor, 512 MB RAM, check user guide for minimum hard drive space, SVGA 800 x 600 with 16-bit colour display, Internet Explorer 5.5 or higher (full install), CD-ROM drive, USB port; Windows Vista®-64: 1 GHz processor, 512 MB RAM, check user guide for minimum hard drive space, SVGA 800 x 600 with 16-bit colour display, Internet Explorer 5.5 or higher (full install), CD-ROM drive, USB port. Mac OS X v10.3, v10.4 and higher; G3, G4, or G5 PowerPC processor; 128 MB RAM; 30 to 50 MB available hard disk space; USB port; CD-ROM drive |
| **Standard software** | Host-based print drivers, TWAIN 1.9 or WIA scanner drivers, scan application, installer/uninstaller, HP MARS/Pony Express usage tracking software, HP Order Reminder, screen fonts, I.R.I.S. Readiris PRO text recognition software (not installed with other software, separate installation required), Mac print drivers and scan drivers. ToolBox and EWS software included. HP LaserJet Scan, HP PC Send/Receive LaserJet Fax, HP Fax Setup Wizard, installer/uninstaller, HP Director (Macintosh). Drivers on the web: Installer, print drivers, HP Send Fax, HP Scan software, HP Toolbox for Fax management and support, HP Software Update |
| **Control panel** | 2-line, 16-character display, alphanumeric buttons, menu and cancel controls, fax, copy controls |
| **Power** | Requirements: Input voltage 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz), 4.5 A; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz), 2.3 A. Consumption: 365 watts maximum (active/printing), 8 watts maximum (ready/sleep), < 0.1 watts maximum (off). Typical electricity consumption (TEC) 1.662 kWh/Week |
| **Dimensions (w x d x h)** | Out of package: 429 x 267 x 338 mm. Packaged: 600 x 333 x 440 mm |
| **Weight** | Out of package: 10 kg. Packaged: 12.3 kg |
| **Printer management** | HP Toolbox FX, HP Embedded Web Server |
| **Operating environment** | Operating temperature: 15 to 32.5° C. Recommended operating temperature: 15 to 32.5° C. Operating humidity: 10 to 80% RH. Operating humidity recommended: 10 to 80% RH. Storage temperature: -20 to 40° C. Storage humidity: 0 to 95% RH. Noise level per ISO 9296: sound power: LwAd 6.3 B(A) (printing), 6.4 B(A) (copy/scan), 3.1 B(A) (ready). Sound pressure: LpAm 50 dB(A) (printing/copy/scan), 16 dB(A) (ready) |
| **Certifications** | CISPR 22: 2005/EN 55022: 2006 Class B, EN 61000-3-2: 2000+A2, EN 61000-3-3: 1995+A1, EN 55024: 1998+A1+A2, FCC Title 47 CFR, Part 15 Class B (USA), ICES-003, Issue 4, (Canada), GB9254-1998, EMC Directive 2004/108/EC with CE Marking (Europe), other EMC approvals as required by individual countries. Regulatory standards: IEC 60950-1 (International), EN 60950-1+A11 (EU), IEC 60825-1+A1+A2, UL/cUL Listed (US/Canada), GS License (Europe), EN 60825-1+A1+A2 (Class 1 Laser/LED Device) GB4943-2001, Low Voltage Directive 2006/95/EC with CE Marking (Europe); other safety approvals as required by individual countries. ENERGY STAR: Yes |
| **Warranty** | One year limited warranty. Warranty and support options vary by product, country and local legal requirements. |

# Ordering information

http://www.hp.com/uk