

# HP Color LaserJet CM4730 MFP series



Workgroup performance soars with this fast, compact, award-winning<sup>1</sup> colour MFP. Get reliable print, copy, fax<sup>2</sup> and send-to functionality at a surprisingly affordable price. Enjoy ease-of-use and access to HP and key partner solutions.

**The perfect tool for mid-volume workgroups of 6 to 15 users in both small and medium businesses and enterprise environments, this fast, colour MFP enables them to be more productive with print, copy, send-to functionality, fax (optional), plus HP and key partner solutions close at hand.**

**Work more effectively with a colour MFP that delivers the functionality you need.**

Get more done with a fast first page out, print and copy speeds of up to 30 ppm for colour and black, two-sided printing at full speed, plus colour scanning. Send and receive documents by adding fax functionality with an internal 33.6 kbps analogue fax card<sup>3</sup>. Facilitate document workflow with embedded send to e-mail functionality, and send to folder and fax with optional HP Digital Sending Software 4<sup>4</sup>. Professional finishing solutions include a stacker/stapler<sup>5</sup> and 3-bin mailbox<sup>6</sup>.

**Keep costs down with an MFP that saves money initially and over time.**

Preserve your budget and still get the functionality you need with this surprisingly affordable MFP which also delivers a low cost per colour page. Control costs when you choose Original HP print cartridges, which feature consistent, high-quality performance that saves your business time and money. Get the benefit of colour with no cost penalty: Colour Access Controls let you monitor colour printing by user or even by application, and choose when and how colour is used in your workgroup

**Now you can focus on your business with an MFP that is easy to use and easy to manage.**

Use, manage and maintain your device with HP's simple, award-winning Easy Select Control Panel. Take advantage of your MFP's features with an intuitive interface that clearly displays all available applications. Enjoy best-in-class networking through the HP Jetdirect Internal Print Server.

Proactively manage your MFP and save valuable IT time with HP Web Jetadmin fleet management software. Original HP Color LaserJet print cartridges with built-in intelligence ensure trouble-free printing.

<sup>1</sup> Buyer's Lab gave HP a "Pick of the Year" award in December 2006 for "Outstanding Achievement for the User Interface Design of its Multifunction Printers"

<sup>2</sup> Fax available with HP Color LaserJet CM4730f MFP, CM4730fsk MFP, and CM4730fm MFP.

<sup>3</sup> Available with HP Color LaserJet CM4730f MFP, CM4730fsk MFP and CM4730fm MFP

<sup>4</sup> HP Digital Sending Software 4 is not included, sold separately  
Software is server based, server required  
Trial included

<sup>5</sup> Available with HP Color LaserJet CM4730fsk MFP only

<sup>6</sup> Available with HP Color LaserJet CM4730fm MFP only.



HP Color LaserJet  
CM4730 MFP



HP Color LaserJet  
CM4730f MFP



HP Color LaserJet  
CM4730fsk MFP



HP Color LaserJet  
CM4730fm MFP

## Series at a glance



### HP Color LaserJet CM4730 MFP

- Print speed of up to 30 ppm colour and black
- 600 dpi resolution
- Imageret 3600
- 384 MB RAM
- 533 MHz processor
- 40 GB hard drive
- USB and parallel port
- EIO slot
- three Flash memory card slots
- standard input capacity of 1600 sheets from 100-sheet MP tray and three 500-sheet trays
- 50-sheet automatic document feeder
- automatic two-sided printing
- Colour Access Controls



### HP Color LaserJet CM4730f MFP

- As base model plus
- 33.6 kbps analogue fax card



### HP Color LaserJet CM4730fsk MFP

- As base model plus
- 33.6 kbps analogue fax card
- stapler/stacker unit



### HP Color LaserJet CM4730fm MFP

- As base model plus
- 33.6 kbps analogue fax card
- three-bin mailbox (for a total output capacity of 700 pages)

## Recommended accessories



**Q7722A**  
HP 256 MB DDR  
200-pin SDRAM DIMM



**Q3701A**  
HP LaserJet MFP Analog  
Fax Accessory 300



**Q7521A**  
HP Color LaserJet  
4730mfp Stapler/Stacker



**Q7523A**  
HP Color LaserJet  
4730mfp 3-bin Mailbox



**T1936AA**  
HP Digital Sending  
Software 4



**C8091A**  
HP Staple Cartridge

## HP Kits



**Q5997A**  
HP LaserJet ADF Maintenance  
Kit



**Q7503A**  
HP 220V Image Fuser Kit  
(150,000 pages)



**J7961G**  
HP Jetdirect 635n IPv6/IPsec  
Internal Print Server (EIO,  
10/100/1000TX)



**J7951G**  
HP Jetdirect ew2400 802.11g  
Wireless and Fast Ethernet  
External Print Server

## Operating and warranty specifications

<b>Operating environment</b>	Operating temperature: 15 to 30° C. Recommended operating temperature: 17 to 25° C. Operating humidity: 10 to 80% RH. Operating humidity recommended: 30 to 70% RH. Storage temperature: -20 to 40° C. Storage humidity: 10 to 90% RH. Noise level per ISO 9296: sound power: LwAd 6.7 B(A) (active, printing); 6.3 B(A) (active, copy or scan); inaudible (ready). Sound pressure: LpAm 50 dB(A) (active, printing); 52 dB(A) (active, copy or scan); inaudible (ready)
<b>Certifications</b>	CISPR 22:2005 / EN 55022:2006 Class A, EN 61000-3-2:2000, EN 61000-3-3:1995, EN 55024:1998, FCC Title 47 CFR, Part 15 Class A / ICES-003, Issue 4 / GB9254-1998, GB17625.1-2003, EMC Directive 89/336/EEC and the Low Voltage Directive 73/23/EEC and carries the CE-Marking accordingly. Regulatory standards: Czech Republic (CSN-IEC 60950-1; IEC 60825-1), Estonia (EEI-EN60950-1; IEC 60825-1), EU (CE Mark-Low Voltage Directive 73/23/EEC), Germany (TUV- EN60950-1; IEC 60825-1), Hungary (MEEI- IEC 60950-1; IEC 60825-1), Lithuania (LS- IEC 60950-1; IEC 60825-1), (Russia (GOST- R50377), Slovakia (IEC 60950-1; IEC60825-1), Slovenia (SQI- IEC 60950-1; EN60825-1), South Africa (IEC 60950-1; IEC60825-1).. ENERGY STAR: Yes
<b>Warranty</b>	One-year warranty

## Ordering information



### HP Color LaserJet CM4730 MFP (CB480A)

HP Color LaserJet CM4730 MFP, power cord, control panel overlay, four print cartridges (one each: black, cyan, magenta, yellow), software drivers and documentation on CD-ROM, information and training CD, in-box documentation (getting started guide, walk up wall poster, telephone support flyer)



### HP Color LaserJet CM4730f MFP (CB481A)

As CM4730 MFP plus analogue fax accessory, and fax install guide



### HP Color LaserJet CM4730fsk MFP (CB482A)

As CM4730 MFP plus analogue fax accessory, fax install guide and stapler/stacker unit



### HP Color LaserJet CM4730fm MFP (CB483A)

As CM4730 MFP plus analogue fax accessory, fax install guide and three-bin mailbox

## Accessories, Supplies and Support

### Accessories

<b>Q7722A</b>	HP 256 MB DDR 200-pin SDRAM DIMM
<b>Q3701A</b>	HP LaserJet MFP Analog Fax Accessory 300
<b>Q7521A</b>	HP Color LaserJet 4730mfp Stapler/Stacker
<b>Q7523A</b>	HP Color LaserJet 4730mfp 3-bin Mailbox
<b>T1936AA</b>	HP Digital Sending Software 4
<b>C8091A</b>	HP Staple Cartridge
<b>Q5997A</b>	HP LaserJet ADF Maintenance Kit
<b>Q7504A</b>	HP Image Transfer Kit (120,000 pages)
<b>Q7503A</b>	HP 220V Image Fuser Kit (150,000 pages)

### Supplies

<b>Q6460A</b>	HP Color LaserJet Q6460A Black Print Cartridge with ColorSphere Toner Approx. 12,000 pages at 5% coverage
<b>Q6461A</b>	HP Color LaserJet Q6461A Cyan Print Cartridge with ColorSphere Toner Approx. 12,000 pages at 5% coverage
<b>Q6462A</b>	HP Color LaserJet Q6462A Yellow Print Cartridge with ColorSphere Toner Approx. 12,000 pages at 5% coverage
<b>Q6463A</b>	HP Color LaserJet Q6463A Magenta Print Cartridge with ColorSphere Toner Approx. 12,000 pages at 5% coverage

### Connectivity

<b>J7961G</b>	HP Jetdirect 635n IPv6/IPsec Internal Print Server (EIO, 10/100/1000TX)
---------------	---

<b>J7951G</b>	HP Jetdirect ew2400 802.11g Wireless and Fast Ethernet External Print Server
---------------	--

### Service & support

<b>HC119A/E</b>	HP Care Pack, 4-Hour, 13x5 Onsite, Hardware Support, 3 years
<b>HC113A/E</b>	HP Care Pack, Next Business Day Onsite, Hardware Support, 3 years
<b>HC115A/E</b>	HP Care Pack, Next Business Day Onsite, Hardware Support, 5 years
<b>HC114A/E</b>	HP Care Pack, Next Business Day Onsite, Hardware Support, 4 years
<b>UC755PA/PE</b>	HP Care Pack, Post Warranty Service, Next Business Day Onsite, Hardware Support, 1 year
<b>UC757PA/PE</b>	HP Care Pack, Post Warranty Service, 4-Hour, 13x5 Onsite, Hardware Support, 1 year
<b>U2010A/E</b>	HP Care Pack, Installation for 1 Network Configuration for Dept and Color LaserJet printer

For a complete list of supplies, accessories and services, please refer to <http://www.hp.com>

## Technical specifications

<b>Print technology</b>	Laser			
<b>Print speed</b>	A4: Up to 30 ppm. First page out black: < 11 sec (from ready) Colour: < 11 sec (from ready). Warm-up time: less than < 165 sec Exact speed varies depending on the system configuration, software program and document complexity.			
<b>Processor</b>	533 MHz. RISC			
<b>Memory</b>	448 MB: 384 MB RAM and 64 MB fixed memory. Expandable to 512 MB RAM, 2 available Flash memory slots for font cards or third-party solutions. Hard Disk Capacity: Standard, 40 GB			
<b>Print</b>	Quality Resolution Printer languages Economical printing	HP ImageREt 3600 Up to 600 x 600 dpi HP PCL 6, HP PCL 5c, HP Postscript level 3 emulation, direct PDF printing (v 1.4), PML (Printer Management Language) Economode, immediate return to Power-safe mode after each print job due to Instant-on fuser technology (saves electricity). Standard automatic two-sided printing and N-up printing (saves paper) 80 internal TrueType fonts scalable in HP PCL and HP Postscript Level 3 emulation; additional font solutions available via Flash memory Up to 175000 pages per month Top: 4.2 mm. Left: 4.2 mm. Right: 4.2 mm. Bottom: 4.2 mm		
<b>Fax</b>	Modem speed Telecom compliance	Up to 33.6 kbps Telecom: TBR-21:1998; EG 201 121:1998, FCC Part 68; CIT certificate per TBR-21 (Croatia); Spec. for Terminal Equipment No. 023/96 (Israel); MoC Tec. Requirements plus GOST Telecom series (Russia); TE001, 003, 006 (South Africa) Standard: 200 x 100 dpi. Superfine: 300 x 300 dpi. Photo: 300 x 300 dpi		
<b>Digital sending</b>	File formats Installation	PDF, JPEG, TIFF, MTIFF Fast Ethernet (standard), Gigabit (optional), 802.11g wireless (optional), Bluetooth wireless (optional)		
<b>Scan</b>	Type Scan resolution Grey scale levels Scannable area	Flatbed, ADF. Colour scanning: Yes Optical: Up to 600 dpi. Enhanced: Up to 600 dpi 256 Minimum media size: 14.8 x 12.7 cm (from ADF). Maximum media size: 12.7 x 14.8 cm (Letter size via the glass), 21.6 x 29.7 cm (Legal size via the ADF) Left: 4.2. Top: 4.2. Right: 4.2. Bottom: 4.2		
<b>Copy</b>	Copy speed Copy resolution Multiple copies Reduce/enlarge	Up to 30 cpm 600 x 600 dpi Up to 999 copies 25 to 400%, 25 to 200% (ADF)		
<b>Media handling</b>	<b>Input:</b> Tray 1  Tray 2  Tray 3  ADF <b>Output:</b> <b>Duplex printing:</b>	<b>Capacity</b> Sheets: 100, envelopes: 20, transparencies: 10 mm stack  Sheets: 500, transparencies: 56 mm stack  Sheets: 500, transparencies: 56 mm stack  Sheets: 50 Sheets: Up to 500. Envelopes: Up to 20 Automatic (standard)	<b>Weight</b> 60 to 220 g/m <sup>2</sup>  60 to 120 g/m <sup>2</sup>  60 to 120 g/m <sup>2</sup>  60 to 120 g/m <sup>2</sup>	<b>Size</b> A4, A5, B5 (JIS), executive (JIS), 16K, D Postcard (JIS), envelopes (DL, C5, B5), custom 76 x 127 to 216 x 356 mm A4, A5, B5 (JIS), executive (JIS), 16K, custom 148 x 210 to 216 x 356 mm A4, A5, B5 (JIS), executive (JIS), 16K, custom 148 x 210 to 216 x 356 mm
<b>Media types</b>	Paper (plain, preprinted, letterhead, prepunched, bond, recycled, colour, light, intermediate, heavy, extra heavy, rough, glossy, heavy glossy, tough), transparencies, labels, envelopes, card stock			
<b>Interface and connectivity</b>	Bidirectional IEEE 1284C parallel port, Hi-Speed USB port (compatible with USB 2.0 specifications), HP Jetdirect Fast Ethernet Embedded Print Server, 1 open EIO slot, foreign interface harness, host USB accessory port. Optional: HP Jetdirect internal and external print servers, HP wireless print servers, Bluetooth wireless printer adapter			
<b>Operating systems compatibility</b>	Windows® 98, 2000, Me, XP Home, XP Professional, Server 2003; Mac OS 9.x and higher; Mac OS X 10.1 or higher, OS/2, UNIX, Linux, HP OpenVMS. Recent printer drivers and software for all supported operating systems are available at <a href="http://www.hp.com/support/ljcm4730mfp">http://www.hp.com/support/ljcm4730mfp</a> . If no access to the Internet, see the support flyer that came in the box with the MFP. Optional: Windows® 2003 and Windows® XP Home and XP Professional; IPsec on IPv4 only on Windows® 2003 and Windows®. Recent printer drivers and software for all supported operating systems are available at <a href="http://www.hp.com/support/ljcm4730mfp">http://www.hp.com/support/ljcm4730mfp</a> .			
<b>Network operating systems compatibility</b>	Microsoft® Windows Vista™ Compatible, Windows Vista™ Premium, XP, Server 2003, XP, 2003 64-bit, XP 64-bit, 2000 (IPv6 only supported on Windows® 2003 and Windows® XP; IPsec on IPv4 only on Windows® 2003 and Windows® XP); Novell 5.1 and later; Apple Mac OS 9.x, OS X 10.2 and later; RED HAT Linux 7.x and later; SUSE Linux 8.x and later; HP-UX 10.20, 11.x, 11.i; Solaris® 2.5 and later (SPARC® systems only); IBM® AIX 3.2.5 and later 1; MPE/iX; Citrix® MetaFrame Server; Windows® Terminal Services. Optional: Windows® 2000, Windows® Server 2003 x86, XP x86, Windows Vista™ x86, Vista x64, Windows® Server 2003 x64, XP x64; Mac OS 10.2 and higher			
<b>Minimum system requirements</b>	Pentium® 90, 16 MB RAM (Windows 98); 133 MHz processor, 64 MB RAM (Windows® 2000); 233 MHz processor, 64 MB RAM (Windows® XP Home, XP Professional); Pentium® 150, 32 MB RAM (Windows® Me); 550 MHz processor, 128 MB RAM (Windows® Server 2003); 220 MB of free hard disk space for Windows®, CD-ROM drive or Internet connection, IEEE 1284-compliant bidirectional parallel port, USB 1.1 port, USB port (compatible with USB 2.0 specifications). Mac OS 9.x, Mac OS X v 10.1 or higher, 160 MB available hard disk space, CD-ROM drive, USB port			
<b>Standard software</b>	Windows® Installer for 2000 and up x86 and x64; Mac Installer for OS 10.2 and higher. Drivers on the web: Printing system; PCL 6 driver only, PCL 5 driver only, Postscript driver only; WJA applet; UPD PCL 6; UPD PCL 5, UPD Postscript; Easy printer care; PC Fax Driver			
<b>Control panel</b>	Touch screen graphical display, job control buttons, numeric keypad, LED status lights			
<b>Power</b>	Requirements: Input voltage 100 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); Input voltage 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz)			
<b>Dimensions (w x d x h)</b>	Out of package: CM4730: 788 x 639 x 1153 mm; CM4730f: 788 x 639 x 1153 mm; CM4730fsk: 1106 x 639 x 1153 mm; CM4730fm: 1106 x 639 x 1153 mm. Packaged: CM4730: 900 x 815 x 1518 mm; CM4730f: 900 x 815 x 1518 mm; CM4730fsk: 900 x 815 x 1636 mm; CM4730fm: 900 x 815 x 1636 mm			
<b>Weight</b>	Out of package: CM4730: 124 kg; CM4730f: 124 kg; CM4730fsk: 136 kg; CM4730fm: 136 kg. Packaged: CM4730: 154.2 kg; CM4730f: 154.2 kg; CM4730fsk: 169.43 kg; CM4730fm: 169.43 kg			
<b>Printer management</b>	HP Embedded Web Server, HP Web Jetadmin, HP Easy Printer Care Software (Web only), HP LaserJet Utility, HP Universal Print Driver			

<http://www.hp.com/uk>



© Copyright Hewlett-Packard Development Company, L.P. 2007. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 03/07 4AA0-9482EEE

